Bac-Bac Mat

Insert for Division 09 Ceilings/Wall Finishes specification section:

PART 1 - GENERAL

1.01 SUBMITTALS

A. Samples: Submit 2 each – 6 to 8 inch sample squares of Bac-Bac Mats showing range of color. [Include 2 each – 12 inch long samples of trim.]

PART 2 - PRODUCTS

2.01 BAC-BAC MATS

- A. Decorative natural matting composed of a chemical composition of banana leaf and cellulose, hemicellulose and lignin trunk fiber, woven with basket weave pattern, hemmed edges[, and Class A fire retardant].
 - 1. Size: 4 by 8 feet sheets, 1/8 to 1/4 inch thick.
 - 2. Color: Wide range of natural browns and tan colors within each sheet.
 - 3. Usage: Interior use only.
 - 4. [Fire Retardant Treatment: Fabricators treatment to achieve Class A rating and be toxin free.]
- B. Source Product: Bac-Bac Mats provided by **amaZulu Inc.**, 1239 Commons Court, Clermont, FL 34711.
 - 1. Telephone: 352.243.5309 / Toll Free: 877.243.5309.
 - 2. Fax: 352.243.5361.
 - 3. Website: www.amazuluinc.com.

PART 3 - EXECUTION

3.01 INSTALLATION - BAC-BAC MATS

A. Install Bac-Bac mats with [contact cement adhesive] [or] [staples]. Trim [perimeter] [and] [seams] using bamboo fabricators [polyester rope] [bamboo slats] [bamboo half rounds].

END