

Faux Bamboo Poles

Insert for Division 06 Finish Carpentry/Millwork specification section:

PART 1 – GENERAL

1.01 SUBMITTALS

- A. Samples: Submit 2 each – 8 inch samples of each size synthetic Bamboo Poles showing joints and range of color specified. [Include end caps.]

PART 2 – PRODUCTS

2.01 FAUX BAMBOO POLES

- B. Decorative prefinished synthetic faux bamboo poles fabricated of fire retardant PVC piping, non-toxic, impervious to rot, decay, aging, or shedding.
 - 1. Size: Diameter as indicated by 10 feet length.
 - 2. Color: [Tan] [Custom color as indicated].
 - 3. Usage: Interior and exterior.
 - 4. [UV resistant coating for exterior use.]
 - 5. [Clear automotive grade sealer coating for exterior use.]
 - 6. [End caps.]
 - 7. Warranty: One year for exterior; unlimited for interior.
- C. Source Product: Faux Bamboo Poles provided by **amaZulu Inc.**, 1239 Commons Court, Clermont, FL 34711.
 - 1. Telephone: 352.243.5309 / Toll Free: 877.243.5309.
 - 2. Fax: 352.243.5361.
 - 3. Website: www.amazuluinc.com.

PART 3 – EXECUTION

3.01 INSTALLATION – FAUX BAMBOO POLES

- A. Column Cover: Cut faux bamboo poles to required length and slide over the pole. Prevent sleeve from rattling by making small holes in the nodes and injecting expanding foam into the cavity. [Install end caps to seal tops.]
- B. Beam Cover: Cut slit in the faux bamboo pole lengthwise and heat in the sun or hot water. Open the pole and stretch around the beam.

END