

Seagrass Mats

Insert for Division 09 Ceilings/Wall Finishes specification section:

PART 1 – GENERAL

1.01 SUBMITTALS

- A. Samples: Submit 2 each – 6 to 8 inch sample squares of Seagrass Mats showing range of colors.[Include 2 each – 12 inch long samples of trim.]

PART 2 - PRODUCTS

2.01 SEAGRASS MATS

- B. Decorative natural matting composed of seagrass woven with herringbone weave pattern, hemmed edges, non-toxic [, and Class A fire retardant].
 - 1. Size: 4 by 8 feet sheets, varies 1/8 – 1/4 inch thick.
 - 2. Color: Varies between beige, tan, and light green.
 - 3. Usage: Interior only.
 - 4. [Fire Retardant Treatment: Fabricators treatment to achieve Class A rating and be toxin free.]
- C. Source Product: Seagrass Mats provided by **amaZulu Inc.**, 1239 Commons Court, Clermont, FL 34711.
 - 1. Telephone: 352.243.5309 / Toll Free: 877.243.5309.
 - 2. Fax: 352.243.5361.
 - 3. Website: www.amazuluinc.com.

PART 3 – EXECUTION

3.01 INSTALLATION – SEAGRASS MATS

- A. Install Seagrass mats with [contact cement adhesive] [or] [staples]. Trim [perimeter] [and] [seams] using bamboo fabricators [polyester rope] [bamboo slats] [sanded and finished bamboo half rounds].

END