

Solid Bamboo Poles

Insert for Division 06 Finish Carpentry/Millwork specification section:

PART 1 – GENERAL

1.01 SUBMITTALS

- A. Samples: Submit 2 each – 8 inch samples of Solid Bamboo Poles showing joints and range of color.

PART 2 – PRODUCTS

2.01 SOLID BAMBOO POLES

- B. Decorative solid bamboo poles with wall thickness between 60 and 99 percent, [lightly sanded with a polyurethane finish] [, and Class A fire retardant].
 - 1. Size: Diameter and length as indicated.
 - 2. Color: Natural coloring between shades of tan and honey.
 - 3. Usage: Interior and exterior.
 - 4. [Fire Retardant Treatment: Fabricators treatment to achieve ASTM E108 Class A rating and be toxin free.]
- C. Source Product: Solid Bamboo Poles provided by **amaZulu Inc.**, 1239 Commons Court, Clermont, FL 34711.
 - 1. Telephone: 352.243.5309 / Toll Free: 877.243.5309.
 - 2. Fax: 352.243.5361.
 - 3. Website: www.amazuluinc.com.

PART 3 – EXECUTION

3.01 INSTALLATION – SOLID BAMBOO POLES

- A. Pre-drill holes in the nodes (thickest part of the bamboo poles) and screw it onto the substrate indicated or attach with a pneumatic nail gun. Hide screws from view using wood putty mixed with bamboo saw dust.

END